



US009638257B2

(12) **United States Patent**  
**Tanimoto**

(10) **Patent No.:** **US 9,638,257 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **ROLLING BEARING APPARATUS**

(56) **References Cited**

(71) Applicant: **JTEKT CORPORATION**, Osaka-shi,  
Osaka (JP)

U.S. PATENT DOCUMENTS

(72) Inventor: **Kiyoshi Tanimoto**, Kashiwara (JP)

2,878,894 A \* 3/1959 Andrews ..... F16C 33/6659

3,743,369 A \* 7/1973 Langstrom ..... F16C 33/3856

4,787,757 A \* 11/1988 Finger ..... F16C 19/385

5,547,060 A \* 8/1996 Giese ..... F16C 19/48

5,749,660 A \* 5/1998 Dusserre-Telmon . F16C 19/166

7,244,096 B2 \* 7/2007 Dins ..... F01D 25/20

415/88

(73) Assignee: **JTEKT CORPORATION**, Osaka-shi  
(JP)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/015,024**

(Continued)

(22) Filed: **Feb. 3, 2016**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2016/0238078 A1 Aug. 18, 2016

JP 2014-062616 A 4/2014

Primary Examiner — Alan B Waits

(30) **Foreign Application Priority Data**

(74) Attorney, Agent, or Firm — Oliff PLC

Feb. 16, 2015 (JP) ..... 2015-027329

(57) **ABSTRACT**

(51) **Int. Cl.**

**F16C 37/00** (2006.01)

**F16C 33/66** (2006.01)

**F16C 33/58** (2006.01)

**F16C 19/06** (2006.01)

(52) **U.S. Cl.**

CPC ..... **F16C 37/007** (2013.01); **F16C 33/586**  
(2013.01); **F16C 33/6681** (2013.01); **F16C**  
**19/06** (2013.01); **F16C 2322/39** (2013.01)

(58) **Field of Classification Search**

CPC .... F16C 33/586; F16C 33/66; F16C 33/6637;  
F16C 33/664; F16C 33/6659; F16C  
33/6677; F16C 33/6681; F16C 19/06;  
F16C 37/007

See application file for complete search history.

A rolling bearing apparatus includes a bearing portion having an outer ring, an inner ring, a plurality of balls, and a cage that holds the balls, and an auxiliary portion provided adjacently to the bearing portion in an axial direction. The auxiliary portion has an auxiliary body portion provided adjacently to the outer ring in the axial direction and an extension portion extending in the axial direction from the auxiliary body portion and interposed between the cage and the inner ring. In the extension portion, a channel is formed that penetrates the extension portion in a direction inclined with respect to a radial direction. The channel is open in an outer peripheral surface of the extension portion, which faces the cage, and in an inner peripheral surface of the extension portion, which faces the inner ring.

**8 Claims, 4 Drawing Sheets**

